

Patent number:

JP6347641

Publication date:

1994-12-22

Inventor:

OTSUKA KIYOTO

Applicant:

KURARAY CO LTD

Classification:

- international:

G02B5/30

- european:

Application number:

JP19930136163 19930607

Priority number(s):

Abstract of JP6347641

PURPOSE:To provide a polarizing film which decreases leaking light in a diagonal direction when the polarizing film is installed in a crossed Nicols state by specifying the double refractive index and thickness of a base material film to respectively specific values.

CONSTITUTION:A polarizing in which a dichromatic dyestuff is adsorbed and oriented on the polyvinyl alcoholic base material film. The thickness of the base material film is 1 to 20mum, more preferably 1 to 13mum. The double refractive index of the base material film is >=0.022, more preferably >=0.025. Further, the base material film is uniformly dyed with the dichromatic dyestuff in the thickness direction. The polarizer has a single layer structure in the thickness direction. The thickness of the polarizer is 2 to 20mum and the degree of polarization is >=99.80%. The case where the double refractive index of the base material film is <0.022 is undesirable as the quantity of the leaking light in the perpendicular direction when the polarizing film is put into the crossed Nicols state attains >=3% even when iodine is adsorbed.

Data supplied from the esp@cenet database - Patent Abstracts of Japan